

Hydraulic Workshop Type Press (WTH-Series)

Model	Capacity	Stroke 'A'	Min Daylight 'B'	Max Daylight 'C'	Daylight Setting 'D'	Width between Column 'E'	Depth between Column 'F'	Overall size G x H x L	Weight approx.
	tons.	mm.	mm.	mm.	mm.	mm.	mm.	mm.	kgs.
WTH-10	10	150	200	650	150	600	150	1000 X 1500 X 500	180
WTH-15	15	150	200	650	150	600	150	1000 X 1500 X 500	200
WTH-20	20	150	200	650	150	800	150	1200 X 1700 X 600	250
WTH-25	25	150	200	650	150	800	150	1200 X 1700 X 700	360
WTH-40	40	150	200	800	150	915	200	1500 X 1900 X 600	500
WTH-50	50	150	200	800	150	915	200	1500 X 1900 X 700	550
WTH-75	75	150	250	1050	200	915	250	1600 X 2100 X 700	600
WTH-100	100	150	250	1050	200	1015	300	1700 X 2300 X 800	900
WTH-150	150	150	250	1050	350	1015	350	1800 X 2400 X 1000	1200
WTH-200	200	150	250	1050	350	1015	400	1850 X 2400 X 1000	1500

Features / Benefits :

- Single acting spring return / Double acting oil return
- Cylinder honed to a surface finish 0.4 microns.
- Hard chrome plated ram to resist scoring and corrosion.
- Wiper to arrest ingress of foreign particles.
- Working pressure 450-700 Bar. • Operated by hand Pump / Power pack
- Mechanical winch and 'V' blocks shall be provided upto 100 T capacity presses only.

