



JCB Excavator 140 >>>



JCB Excavator 200 >>>



Model	Capacity	Stroke	Throat of 'C' Frame	Height of 'C' Frame	Daylight of 'C' Frame	Total Weight Approx
	Tons	MM	MM	MM	MM	Kgs.
PTP 50	50	100	90	300	350	100
PTP 100	100	125	90	320	400	200
PTP 150	150	300	90	330	400	300

Application :

To remove & Install master pins, track pins & master bushes, of all types of excavators / Dozers

Features / Benefits :

- Portable and can be performed at site and shop floor application. • Small crane / Hydra is required for handling during operation.
- Avoid old age method of strenuous sledge hammering during removal and insertion of master pin
- Avoid gas cutting of chain segment for removal of master pin.
- Alloy Steel casting 'C' frame with hardened alloy steel bushes.
- Noise less in operation. • QCC with Plastic dust cap. Aluminium Dust Cap on Request.

POWERJAC Systems Pvt. Ltd.

Regd. Off./Factory: Plot B-25, Survey no.329, off Majgaon Cross, Khanapur Road, Udyambag, Belgaum - 590 008. KARNATAKA. INDIA. Phone : +91-831-2442565
Telefax : +91-831-2445565 E-mail : response@powerjac.com / sales@powerjac.com

Nearest Distributor :