

Plain Ram, Center Hole, Double Acting Hydraulic Jack

Capacity : 30-100 tons Stroke : 100-150 mm Working Pr.: 700 bar (Max.)

Model	Capacity	Closed Ht. 'CH'	Stroke 'S'	Ram Dia 'RD'	Outer Dia 'D'	Centre Hole Dia 'C'	Oil Volume	Approx. Weight	Suitable Hand pump
	Tons	MM	MM	MM	MM	MM	C.C.	KG.	
CHD 30/150	30	320	150	63	130	34	663	26	PHP 400/3N
CHD 50/150	50	330	150	95	170	42	1178	43	PHP 500/6
CHD 60/150	60	350	150	115	190	54	1560	68	PHP 500/6
CHD 80/150	80	360	150	130	205	62	1840	82	PHP 500/6
CHD 100/150	100	370	150	150	230	77	2310	102	PHP 500/6

Features / Benefits :

- High strength, Heat treated alloy steel body for better life.
- Hard chrome plated ram to resist scoring and corrosion.
- Double acting for push full application. ● Wiper to arrest ingress of foreign particles.
- Bigger center hole designed allows to run screws/cables/studs to pull or push forces.
- High pressure long life seals. QCC with Plastic dust cap. Aluminium Dust Cap on Request.
- Bottom mounting holes for fixturing different types of puller attachments.
- Custom strokes available on request.
- Port size 3/8" inch NPT.

Application :

These jacks are designed to attach various puller attachments for removing gears, bearings, pulleys, pre-stressing at construction projects

